

AirBORNE™

TXP-2D High Frequency Ventilator



Small and lightweight
Only high frequency transport ventilator
Compatible with INO therapy

AirBORNE™

TXP-2D High Frequency Ventilator

Technical Specifications

Standard Features	Compatible versions for both the AirBorne™ Voyager and AirBorne™ Aviator Transport Systems Adds the additional capability of high frequency ventilation Compatible with the AeroNOx™ Nitric Oxide delivery system Configurable for ambulance as well as rotary and fixed wing aircraft	
Dimensions	Voyager (vertical mount) version	24.1 cm H x 11.4 cm W x 10.2 cm D
	Aviator (horizontal mount) version	11.4 cm H x 24.1 cm W x 10.2 cm D
Weight	2.3 kg	
Internal Battery	4 AA batteries for frequency counter	
Gas Consumption	10 to 15 lpm	
Frequency / Rates	Rate	I:E
	450+	1:1
	350-450	1:1.5
	250-350	1:2
Mean Airway Pressure	30 cm H ₂ O	

Additional Options Available

Phasitron Circuit	Part Number 731-8602
--------------------------	----------------------

Worldwide

International Biomedical

8206 Cross Park Drive, Austin, Texas USA 78754
T. +1.512.873.0033 F. +1.512.873.9090
sales@int-bio.com

Europe

International Biomedical AG

Glütschbachstrasse 2, CH-3661 Uetendorf, Switzerland
T. +41.33.345.66.00 F. +41.33.345.66.08
welcome@int-bio.ch

int-bio.com

International Biomedical reserves the right to make changes in specifications and features shown herein or discontinue the product described at any time without notice or obligation. Contact your representative for the most current information.