

AeroNOx™

Nitric Oxide Delivery

NOx on the go



Compact and portable
NO and NO₂ monitoring
Built-in sampling system
Audible and visual alarms

Technical Specifications

Standard Features	Light weight, portable design Continuous delivery of inhaled Nitric Oxide Monitors NO, NO ₂ , and O ₂ Backlit, digital readout Long battery life Push button zeroing Compatible with conventional and Bronchotron® / TXP-2D® high frequency ventilation
Audible and Visual Alarms	NO high / low NO ₂ high 1 minute silence feature
Display	Backlit LCD main screen LED indicators
Visual Indicators	NO and NO ₂ in ppm O ₂ % NO delivery flow rate in lpm Battery indicator Sample line occlusion
Operating Temperature Range	40° F to 104° F
Atmospheric Range	0 ft to 12,000 ft
Dimensions	10 in H x 12 in W x 5 in D
Weight	11.7 lbs
Gas Supply	Compatible with standard and portable Nitric Oxide cylinders with CGA 626 fittings
Gases Detected	Nitric Oxide (NO) Nitrogen Dioxide (NO ₂) Oxygen (O ₂)
Concentration Range	NO 0 to 100 ppm NO ₂ 0 to 12 ppm O ₂ 5 to 100%
NO Mass Flowmeter	0 to 2 lpm, 10 cc/min resolution
Calibration	Push button zeroing and simple high range calibration
Sensors	Electrochemical
AC Power	Universal AC adaptor, 100-240V AC, 50-60 Hz, 0.75-0.35A
Internal Battery	One, 6V, 4.5 amp-hour sealed, lead acid type with auto recharge 5 hours fully charged

Worldwide

International Biomedical

8206 Cross Park Drive, Austin, Texas USA 78754
T. 512.873.0033 F. 512.873.9090
sales@int-bio.com

Europe

International Biomedical AG

Glütschbachstrasse 2, CH-3661 Uetendorf, Switzerland
T. +41.33.345.66.00 F. +41.33.345.66.08
welcome@int-bio.ch

int-bio.com

International Biomedical reserves the right to make changes in specifications and features shown herein or discontinue the product described at any time without notice or obligation. Contact your representative for the most current information.