

AeroNOx 2.0™

Nitric Oxide Delivery

Nitric Oxide Delivery System



NICU



Air



Ground

Meets transport standards
Lightweight and rugged
NO, NO₂ and O₂ monitoring

Compatible with TXP High Frequency Ventilator

AeroNOx 2.0™

Nitric Oxide Delivery

Technical Specifications

| | |
|------------------------------------|---|
| Standard Features | Lightweight, portable design Continuous delivery of inhaled Nitric Oxide Monitors NO, NO ₂ , and O ₂ Color screen Long battery life |
| Audible and Visual Alarms | O ₂ high / low NO high / low NO ₂ high 1 minute silence feature |
| Display | 4.5 in color screen |
| Visual Indicators | NO and NO ₂ in ppm O ₂ % NO delivery flow rate in L/min Battery indicator Sample line occlusion |
| Operating Temperature Range | 32° F to 102° F |
| Atmospheric Range | 0 ft to 12,000 ft |
| Dimensions | 9.8 in H x 13 in W x 5.5 in D |
| Weight | 8.8 lb |
| Gas Supply | Compatible with standard and portable Nitric Oxide cylinders with CGA 626 fittings |
| Gases Detected | Nitric Oxide (NO) Nitrogen Dioxide (NO ₂) Oxygen (O ₂) |
| Concentration Range | NO: 0 to 99 ppm NO ₂ : 0 to 9 ppm O ₂ : 18 to 100% |
| NO Mass Flowmeter | 0 to 2 L/min, 0.01 L/min resolution |
| Calibration | Simple zeroing and simple high range calibration |
| Sensors | Electrochemical |
| AC Power | Universal AC adapter, 120-240V AC, 50-60 Hz |
| Internal Battery | One 6V, 4.5 amp-hour sealed, lead acid type with auto recharge 5 hours fully charged |

Worldwide

International Biomedical

8206 Cross Park Drive, Austin, Texas USA 78754
T. 512.873.0033 F. 512.873.9090
sales@int-bio.com

Europe

International Biomedical AG

Glütschbachstrasse 100, CH-3661 Uetendorf, Switzerland
T. +41.33.345.66.00 F. +41.33.345.66.08
welcome@int-bio.ch

int-bio.com

International Biomedical reserves the right to make changes in specifications and features shown herein or discontinue the product described at any time without notice or obligation. Contact your representative for the most current information.